

PVC
OVERLAY PANELS

www.ekookna.com

PVC
OVERLAY PANELS

The pinnacle of design, functionality, thermal insulation, and acoustic insulation.

U_p = up to 0,5 W/m²K

Height:	1500 - 2270* mm
Width:	500 - 990 mm
Thickness:	36 - 70 mm

*2280 for lacquered panels

The panel consists of a GFK surface plate, a core (thermally insulated sandwich with reinforcement), and an HPL plate on the inside.







Finishes

- Decorative pilasters (grooving) in any RAL K5 Classic color on the exterior side of the door
- Stainless steel applications, black or silver, fully integrated into the panel (depending on the model)
- Handles mounted in the body of the infill or recessed

Panel cladding or painting in RAL K5 Classic colors*

- Independent finishing for the interior and exterior sides
- The possibility of using two different colors on selected panels

Glazing

- Availability of glazing configurations depends on the selected panel
- Up to triple-glazed units
- A wide selection of decorative and solar control glass
- Easy replacement of damaged glass

*The catalog of veneers is constantly updated.

PVC **OVERLAY PANELS**

- High-quality workmanship
- Sandwich-type core with hard foam insulation and reinforcements
- GFK - single-sided overlay
- Wide range of decorative films



AIDA ET



AMANDA ET



AMELIE ET



ANETA ET



ANGELIKA ET



BARBARA ET



BRIGITTE ET



DENISA ET



DONATELA ET



DORIS ET



ESTER ET



FLAVIA ET



FLORA ET



GITA ET



IDA ET



ISABELA ET



KIM ET



KIRA ET



LAURA ET



LILY ET



MANON ET



MARION ET



MEGAN ET



MILENA ET



MIRANDA ET



MIRIAM ET



MIRKA ET



NELA ET



ODETTE ET



PATRICIE ET



PENELOPE ET



RADANA ET



RAISA ET



ROSALIE ET



SARAH ET



SOFIE ET



TANIA ET

This publication does not constitute a commercial offer. It is not a basis for complaints.
The presented photos are illustrative images and not actual photos of the products.